


# NFPA 1971 Gloves for Firefighters



from



**INNO**®  
TEX



**SunbeltFire**

*Serving you is our calling™*

Kent Bradley · Ext. 106 · [kbradley@sunbeltfire.com](mailto:kbradley@sunbeltfire.com)  
Stacy Lay · Ext. 107 · [slay@sunbeltfire.com](mailto:slay@sunbeltfire.com)

**800-642-8484 | [www.SunbeltFire.com](http://www.SunbeltFire.com)**

## SPECIFICATION SHEET - INNO735™



### **Glove shall meet or exceed the following Minimum Requirements:**

- Glove shall meet or exceed the requirements of NFPA 1971.
- Five-finger glove style shall have natural anatomically correct thumb to finger movement. Straight-thumb and Wing-thumb styles not acceptable.
- Outer shell:
  - Palm and back-knuckle shall be made of Black Eversoft split cowhide for durability and long lasting softness, even after repeated use and laundering.
  - Back of hand shall be made of Gold Elkskin for best dexterity.
  - Glove shall have a kangaroo leather strap sewn across the entire palm for extra protection and superior grip.
  - Knitted Kevlar shall not be used in the outer shell.
- Glove shall not have a separate sewn-on cuff or gauntlet.
- Back of hand shall be three separate pieces with knuckle piece slightly bowed to fit the natural curvature of the hand when relaxed.
- Glove insert shall be a highly breathable PYROTECT® insert only.
- Glove insert shall be stitched and bonded to leather shell for permanent attachment and be warranted for no liner pull-out.
- Caulked or glued barrier seams shall not be permitted.
- Thermal lining shall be a soft SEF fabric and have a special sewn back of hand Flex-Dart for added dexterity.
- Outer shell shall be sewn with a minimum Tex 80 Kevlar thread.
- Thermal lining shall be sewn with Nomex thread.
- All seams in the outer shell and thermal lining shall be lock-stitched. Chain-stitch shall not be used.
- ½" Heavy duty elastic shall be sewn zig-zag around the entire glove at wrist.
- Glove shall be available in the following sizes:
  - Regular: XXS, XS, S, M, L, XL, and XXL.
  - Cadet: L, and XL.
  - Special Sizes for 3XL or greater or missing digits shall be made available.
- Wristlet style shall be available
  - 2 layers of black Nomex® knit, 1½ inches long, ± ¼ inch.
- Glove shall be MADE IN USA



## SPECIFICATION SHEET - INNO775™



### Glove shall meet or exceed the following Minimum Requirements:

- Glove shall meet or exceed the requirements of NFPA 1971.
- Glove shall be made with a TRU-3D™ glove style shall have kangaroo leather fourchettes on the sides of all fingers and thumb, from cuff to cuff.
- Five-finger glove style shall have natural anatomically correct thumb to finger range of motion. Straight-thumb and Wing-thumb styles are not acceptable.
- Outer shell:
  - Palm shall be made of Black Eversoft split cowhide for durability and long lasting softness, even after repeated use and laundering.
  - Back of hand shall be made of Gray Elkskin for best dexterity.
  - Back-knuckle shall be made of kangaroo leather.
  - Knitted Kevlar shall not be used in the outer shell.
- Glove shall not have a separate sewn-on cuff or gauntlet.
- Back of hand shall be made of three separate pieces with the kangaroo leather knuckle piece slightly bowed to fit the natural curvature of the hand when relaxed.
- Glove insert shall be PYROPRO™ for breathability and dexterity as well as added radiant heat protection on the back of the hand.
- Glove insert shall be stitched and bonded to leather shell for permanent attachment and be warranted for no liner pull-out.
- Caulked or glued barrier seams are not permitted.
- Thermal lining shall be Nomex/Kevlar stitch-bonded fabric and have a special sewn back of hand Flex-Dart for added dexterity.
- Outer shell shall be sewn with a minimum Tex 80 Kevlar thread.
- Thermal lining shall be sewn with Nomex thread.
- All seams in the outer shell and thermal lining shall be lock-stitched. Chain-stitch shall not be used.
- ½" Heavy duty elastic shall be sewn zig-zag around the entire glove at wrist.
- Glove shall be available in the following sizes:
  - Regular: XXS, XS, S, M, L, XL, and XXL.
  - Cadet: L, and XL.
  - Special Sizes for 3XL or greater or missing digits must be made available.
- Wristlet style shall be available
  - 2 layers of black Nomex® knit, 1½ inches long, ± ¼ inch.
- Glove shall be MADE IN USA



Kent Bradley · Ext. 106 · [kbradley@sunbeltfire.com](mailto:kbradley@sunbeltfire.com)  
Stacy Lay · Ext. 107 · [slay@sunbeltfire.com](mailto:slay@sunbeltfire.com)

**800-642-8484 | [www.SunbeltFire.com](http://www.SunbeltFire.com)**



## SPECIFICATION SHEET - INNO795™



### Glove shall meet or exceed the following Minimum Requirements:

- Glove shall meet or exceed the requirements of NFPA 1971.
- Glove shall be made with a TRU-3D™ glove style shall have textured kangaroo leather fourchettes on the sides of all fingers and thumb, from cuff to cuff.
- Five-finger glove style shall have natural anatomically correct thumb to finger range of motion. Straight-thumb and Wing-thumb styles are not acceptable.
- Outer shell:
  - Palm and back of hand shall be made of kangaroo leather for superior durability, grip, and minimal water absorption.
  - Back-knuckle shall be made of textured kangaroo leather.
  - Knitted Kevlar shall not be used in the outer shell.
- Glove shall not have a separate sewn-on cuff or gauntlet.
- Back of hand shall be made of three separate pieces with the textured kangaroo leather knuckle piece slightly bowed to fit the natural curvature of the hand when relaxed.
- Glove insert shall be PYROPRO™ for breathability and dexterity as well as added radiant heat protection on the back of the hand.
- Glove insert shall be stitched and bonded to leather shell for permanent attachment and be warranted for no liner pull-out.
- Caulked or glued barrier seams are not permitted.
- Thermal lining shall be Nomex/Kevlar stitch-bonded fabric and have a special sewn back of hand Flex-Dart for added dexterity.
- Outer shell shall be sewn with a minimum Tex 80 Kevlar thread.
- Thermal lining shall be sewn with Nomex thread.
- All seams in the outer shell and thermal lining shall be lock-stitched. Chain-stitch shall not be used.
- ½" Heavy duty elastic shall be sewn zig-zag around the entire glove at wrist.
- Glove shall be available in the following sizes:
  - Regular: XXS, XS, S, M, L, XL, and XXL.
  - Cadet: L, and XL.
- Special Sizes for 3XL or greater or missing digits must be made available
- Wristlet style shall be available
  - 2 layers of black Nomex® knit, 1½ inches long, ± ¼ inch.
- Glove shall be MADE IN USA



Kent Bradley · Ext. 106 · [kbradley@sunbeltfire.com](mailto:kbradley@sunbeltfire.com)  
Stacy Lay · Ext. 107 · [slay@sunbeltfire.com](mailto:slay@sunbeltfire.com)

**800-642-8484 | [www.SunbeltFire.com](http://www.SunbeltFire.com)**